



Easy-Licensed Band (UHF) Walky-Talky

- 16 CHANNELS
- VOICE CHANNEL ANNUNCIATION
- HIGH/LOW POWER SWITCHABLE
- 50 CTCSS/104 CDCSS ENCODE & DECODE
- AUTO BATTERY SAVE
- LOW BATTERY ALERT
- BUSY CHANNEL LOCKOUT
- TIME-OUT TIMER (TOT)
- EMERGENCY ALARM

D-36



D-36

PROFESSIONAL FM TRANSCEIVER

Transmitter

Frequency Range	350 MHz
Channel Capacity	16
Operating Voltage	7.4V LI-ION
Working temperature	-20°C - +60°C
Frequency Stability	± 2.5 ppm
Dimension (Height x length x width)	100 x 55.5 x 31 mm
Weight	200g

Transmitter

Power output	4W / 1W
Modulation type	F3E
Spurious Radiation	< -60dB
Adjacent Channel Power	> 65dB
Modulation Limitation	± 5KHz
Modulation Distortion	≤ 5%
Signal Noise	40dB
Modulation Function	±3dB

Receiver

Sensitivity	< 0.20 μV
Adjacent Channel Sensitivity	65dB
Spurious Response Rejection	65dB
Audio power	500mW
Audio Distortion	≤ 5%
Audio Distortion	≥ 60dB

Accessories



Omega Airlink Solutions (P) Limited
 (An ISO 9001:2008 Certified Company)
 Plot No. 1 | Executive Club Road
 Chandanhula | Chattarpur | New Delhi – 110 074
 Helpline : +91 11 6515 9136
 info@omegaairlink.com

Authorized Dealer: